26/05/2022

TRUCK TIRE CHANGERS



SUBJECT: TECO58M - New semi-automatic truck tire changer

We are pleased to present you our new model **Teco58M**: a **semi-automatic** truck tire changer for truck, bus, tractor and earthmoving machines wheels.

This semi-automatic model was created as a completion of the automatic version Teco58A currently in production, and is characterized by the same solidity, reliability and versatility of use.

In the new version, the tools lifting and rotation are mechanically operated by solid and robust hooking and unhooking devices, having an ergonomic design and which are operated manually.



14" - 58" clamping2 speed rotation with self-braking electric motor



Manual tool rotation





management





26/05/2022

TRUCK TIRE CHANGERS

MAIN FEATURES:

- Clamping capacity 14" ÷ 58" for clamping rims of trucks, busses, tractors and earth moving machines
- 2-speed chuck rotation to reduce bead breaking times
- Self-braking chuck motor to ensure maximum precision during the most delicate working phases
- Synchronized chuck and tool-holder carriages movement to have the tire always in an optimal working position
- 2-speed translational movement to sensibly reduce operator working time
- 30.000N bead breaking force, useful on the most critical tires
- The tools rotation is manually operated by a solid and ergonomic lever with automatic hooking
- The tools lifting and lowering are manually operated, with automatic hooking and solid fixing to the tool carriage
- Pre-fitted for wireless remote control thanks to a practical radio kit that can be installed on the machine on request, also compatible with Teco55
- Power unit Stand-By function for energy saving

STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES

PAR - Clamp for alloy rims	801227195
JAR-2 - Set of 4 jaws for alloy rims	8-12100156



26/05/2022

TRUCK TIRE CHANGERS

T56 - Tubeless roller	801280918
TR-2 - Set of 4 extensions from 48" to 58"	8-12100155
RC TROLLEY - Radio remote control	8-12120025/00

New machine part numbers to be use when ordering:

P/N	VOLTAGE	
0-12400901/00	400V/3Ph/50Hz	
0-12400902/00	230V/3Ph/60Hz	
0-12400903/00	400V/3Ph/60Hz	

Available in following standard colour version

CONFIGURATION CODE	COLOUR
/16	RAL 3002

Please refer to the current price list for the complete list of available optional accessories.