

# EXPORT CATALOGUE

# C-Line Lifting Equipment

& Original Accessories



EFFECTIVE FROM JANUARY 2024 REL. MARCH 2024




### **COLOR TABLE**

1) The standard company color of our lifting equipment is red RAL 3002 (-> /16 or /15) and grey RAL 7016 ( /34).

#### WARNING

THE CUSTOMIZATION KIT IS COMPULSORY AND MUST BE ALWAYS ORDERED TOGETHER WITH THE PART-NO. OF THE SELECTED LIFT.











TECO HC5502 TECO HC4502 COMPULSORY ACCESSORIES - TECO HC5502 - TECO HC4502 OPTIONAL ACCESSORIES - TECO HC5502 - TECO HC4502 TECO HC4502 B TECO HC3502 B COMPULSORY ACCESSORIES - TECO HC4502 B - TECO HC3502 B OPTIONAL ACCESSORIES - TECO HC4502 B - TECO HC3502 B	4 4 5 6 6 7 8 9
ELECTRO-HYDRAULIC UNDERBODY SCISSORS TYPE LIFTS TECO C360 B TECO C320 B COMPULSORY ACCESSORIES - TECO C360 B - TECO C320 B OPTIONAL ACCESSORIES - TECO C360 B - TECO C320 B	10 10 11 12 12
DOUBLE SCISSORS LIFTS - LOW PROFILE TECO C322 EF TECO C362 EF COMPULSORY ACCESSORIES - TECO C322 EF - TECO C362 EF OPTIONAL ACCESSORIES - TECO C322 EF - TECO C362 EF	14 14 15 16
DOUBLE SCISSORS LIFTS - HIGH PROFILE TECO C372   E TECO C412   E COMPULSORY ACCESSORIES - TECO C372   E - TECO C412   E OPTIONAL ACCESSORIES - TECO C372   E - TECO C412   E	18 18 19 20 20
PLATFORM SCISSORS LIFTS FOR WHEEL ALIGNMENT - LOW PROFILE TECO 5500C TECO 4500C OPTIONAL ACCESSORIES - TECO 5500C - TECO 4500C	22 22 24 26













- -Capacity: 5.500 kg.
- -Possibility of installation in symmetrical or asymmetric version.
- -Lifting system: with hydraulic cylinders and synchronisation with wire ropes on the column top.
- -Standard height of two-post connection: 4,050 mm.
- -Single motor.
- -Electro magnet safety release 24V.
- -Three-stage symmetric arms with pads adjustable in height and extensions supplied as standard.
- -Anticrushing safety bar as standard.
- -Minimum lifting height: 100 mm.
- -Maximum lifting height: 2.080 mm.



Also available versions (with optional column extension set):

-V: High version specific for vans

(Height of two-post connection: 4.620 mm).

-XV: Extra-above version specific for vans and very high vehicles (Height of two-post connection: 5.220 mm).



Code	Power Supply	Description	
0-43107700/15	400V / 3Ph / 50-60Hz	TECO HC5502 Red RAL 3002 Orange peel	
0-43107702/15	230V / 1Ph / 50Hz	TECO HC5502 Red RAL 3002 Orange peel	
0-43107703/15	230V / 1Ph / 60Hz	TECO HC5502 Red RAL 3002 Orange peel	
8-43600216		Customization kit (Compulsory)	





### **ELECTRO-HYDRAULIC TWO POST LIFTS**









- -Capacity: 4.500 kg.
- -Possibility of installation in symmetrical or asymmetric version.
- -Lifting system: with hydraulic cylinders and synchronisation with wire ropes on the column top.
- -Standard height of two-post connection: 4,050 mm.
- -Single motor.
- -Electro magnet safety release 24V.
- -Three-stage symmetric arms with pads adjustable in height and extensions supplied as standard.
- -Anticrushing safety bar as standard.
- -Minimum lifting height: 100 mm.
- -Maximum lifting height: 2.080 mm.



Also available versions (with optional column extension set):

-V: High version specific for vans

(Height of two-post connection: 4.620 mm).

-XV: Extra-above version specific for vans and very high vehicles (Height

of two-post connection: 5.220 mm).



Code	Power Supply	Description	
0-43107800/15	400V / 3Ph / 50-60Hz	TECO HC4502 Red RAL 3002 Orange peel	
0-43107802/15	230V / 1Ph / 50Hz	TECO HC4502 Red RAL 3002 Orange peel	
0-43107803/15	230V / 1Ph / 60Hz	TECO HC4502 Red RAL 3002 Orange peel	
8-43600217		Customization kit (Compulsory)	







COMPULSORY ACCESSORIES - TECO HC5502 - TECO HC4502			
Image Description Code			
	Set of masonry screws (16 pcs.). For all models in the range	8-43100161	

OPTIONAL ACCESSORIES - TECO HC5502 - TECO HC4502			
Image	Description	Code	
	Column extension set L = 570 mm - (H = 4.620 mm)*.	8-43100224/15	
The state of the s	Column extension set L = 1.170 mm - (H = 5.220 mm)*.	8-43100225/15	
	Pompa manuale discesa d'emergenza (raccomandato).	8-43100205	





# **ELECTRO-HYDRAULIC TWO POST LIFTS**









- -Capacity: 4.500 kg.
- -Single motor.
- -Lifting system: with hydraulic cylinders and synchronisation with wire ropes on the column base.
- -Three-stage asymmetric arms with pads adjustable in height and extensions supplied as standard.
  -Minimum lifting height: 95 mm.
  -Maximum lifting height: 1.945 mm





Code	Power Supply	Description	
0-43107400/48	400V / 3Ph / 50-60Hz	TECO HC4502 B Grey RAL 7040 Orange peel	
0-43107402/48	230V / 1Ph / 50Hz	TECO HC4502 B Grey RAL 7040 Orange peel	
0-43107403/48	230V / 1Ph / 60Hz	TECO HC4502 B Grey RAL 7040 Orange peel	
8-43600214		Customization kit (Compulsory)	
		Other colors than the standard are NOT currently provided	





# **ELECTRO-HYDRAULIC TWO POST LIFTS**



# COHC3502 B





Main features:

-Capacity: 3.500 kg.


-Single motor.

-Lifting system: with hydraulic cylinders and synchronisation with wire ropes on the column base.

-Three-stage asymmetric arms with pads adjustable in height and extensions supplied as standard.

-Minimum lifting height: 95 mm.

-Maximum lifting height: 1.945 mm



Code	Power Supply	Description	
0-43107500/48	400V / 3Ph / 50-60Hz	TECO HC3502 B Grey RAL 7040 Orange peel	
0-43107502/48	230V / 1Ph / 50Hz	TECO HC3502 B Grey RAL 7040 Orange peel	
0-43107503/48	230V / 1Ph / 60Hz	TECO HC3502 B Grey RAL 7040 Orange peel	
8-43600212		Customization kit (Compulsory)	
		Other colors than the standard are NOT currently provided	







COMPULSORY ACCESSORIES - TECO HC4502 B - TECO HC3502 B			
mage Description Code			
	Set of masonry screws (10 pcs.) For all models in the range.	8-43100233	

OPTIONAL ACCESSORIES - TECO HC4502 B - TECO HC3502 B			
Image	Description	Code	
	Main frame kit RAL7016 (To be order in case of location with critical floors).	8-43100222	
	Manual emergency descent pump.	8-43100205	





## **ELECTRO-HYDRAULIC UNDERBODY SCISSORS TYPE LIFTS**









- -Capacity: 3.600 kg.
- -For tyre specialists, car workshops and body repairers.
- -Alignment of the runways by 2 anti-torsion connection bars.
- -Built-in ascent and descent ramps to the runways.
- -Automatic engagement of mechanical safety locks with pneumatic release system.
- -Equipped with anti-crushing foot guard.
- -Low voltage control unit with «dead-man» control system.
- -Low profile configuration for on-floor installations.
- -Runboard height from ground: 115 mm.
- -Max. lifting height: 1000 mm.
- -Runboard length: 2.040 (open ramps)





All models supplied with:
-1 Set of 4 hard rubber blocks



Code	Power Supply	Description	
0-41106600/15	230/400V - 3Ph - 50/60Hz	TECO C360 B Red RAL 3002 Orange peel	
0-41106602/15	230V - 1Ph - 50Hz	TECO C360 B Red RAL 3002 Orange peel	
0-41106603/15	230V - 1Ph - 60Hz	TECO C360 B Red RAL 3002 Orange peel	
8-41600195		Customization kit (Compulsory)	





## **ELECTRO-HYDRAULIC UNDERBODY SCISSORS TYPE LIFTS**



# CC 320 B





- -Capacity: 3.200 kg.
- -For tyre specialists, car workshops and body repairers.
- -Alignment of the runways by 2 anti-torsion connection bars.
- -Built-in ascent and descent ramps to the runways.
- -Automatic engagement of mechanical safety locks with pneumatic release system.
- -Equipped with anti-crushing foot guard.
- -Low voltage control unit with «dead-man» control system.
- -Low profile configuration for on-floor installations.
- -Runboard height from ground: 115 mm.
- -Max. lifting height: 1000 mm.
- -Runboard length: 2.040 (open ramps)





Code	Power Supply	Description	
0-41106500/15	230/400V - 3Ph - 50/60Hz	TECO C320 B Red RAL 3002 Orange peel	
0-41106502/15	230V - 1Ph - 50Hz	TECO C320 B Red RAL 3002 Orange peel	
0-41106503/15	230V - 1Ph - 60Hz	TECO C320 B Red RAL 3002 Orange peel	
8-41600194		Customization kit (Compulsory)	





-1 Set of 4 hard rubber blocks



COMPULSORY ACCESSORIES - TECO C360 B - TECO C320 B			
Image	Description	Code	
	Set of masonry screws (8 pcs.) For all models in the range.	8-41100203	

OPTIONAL ACCESSORIES - TECO C360 B - TECO C320 B			
Image	Description	Code	
	M320 Moving wheel set for mobile version. Available for model TECO C320 B only.  NOTE: The lift with the mounted accessory is downgraded to 3000 kg. and is not reversible	8-41100320	
	Crossbar set (2 bars and 4 pads), L=1800 mm.	8-42300047	
	<b>Pad set</b> (4 pcs.) H = 80 mm.	8-42300027	







OPTIONAL ACCESSORIES - TECO C360 B - TECO C320 B			
Image	Description	Code	
	Long ramps for vehicles with spoiler having length 1.200 mm (4 pcs)	8-44600003	





## **DOUBLE SCISSORS LIFTS - LOW PROFILE**



**COC**322 EF





#### Main features:

- -Capacity: 3.200 kg.
- -Electrohydraulic underbody double scissors type lift, for tyre specialists, car workshops, and body repairers.
- -Alignment of the runways with a dual MASTER/SLAVE circuit (two cylinders per runboard) without mechanical safety racks.
  -Runboards version with flaps (F) only.
  -All models available in both on-floor and flush installation
- versions.



Code	Power Supply	Description	
0-41106000/15	230/400V - 3Ph - 50/60Hz	TECO C322 EF	
0-41106002/15	230V - 1Ph - 50Hz	TECO C322 EF	
0-41106003/15	230V - 1Ph - 60Hz	TECO C322 EF	
8-41600189		Customization kit (Compulsory)	





## **DOUBLE SCISSORS LIFTS - LOW PROFILE**









#### Main features:

- -Capacity: 3.600 kg.
- -Electrohydraulic underbody double scissors type lift, for tyre specialists, car workshops, and body repairers.
- -Alignment of the runways with a dual MASTER/SLAVE circuit (two cylinders per runboard) without mechanical safety racks.
- -Runboards version with flaps (F) only.
  -All models available in both on-floor and flush installation versions.



Code	Power Supply	Description	
0-41106100/15	230/400V - 3Ph - 50/60Hz	TECO C362 EF	
0-41106102/15	230V - 1Ph - 50Hz	TECO C362 EF	
0-41106103/15	230V - 1Ph - 60Hz	TECO C362 EF	
8-41600190		Customization kit (Compulsory)	







COMPULSORY ACCESSORIES - TECO C322 EF - TECO C362 EF			
Image	Description	Code	
	Set of masonry screws (8 pcs.) For all models in the range.	8-41100203	

OPTIONAL ACCESSORIES - TECO C322 EF - TECO C362 EF		
Image	Description	Code
	Off-the-road vehicle cross bar (2 pcs).	8-42300047
	Flush installation frame set (galvanized) for C-line underbody low profile double scissor lifts with flaps (must be combined with 8-41100165)	8-41100225







OPTIONAL ACCESSORIES - TECO C322 EF - TECO C362 EF				
Image	Description	Code		
	Set of long ramps for on-floor version.  L = 1000 mm	8-41100207		
	Extensions for pipes and cables L= 1 mt (protection covers included)	8-41100184		
	Extensions for pipes and cables L= 2 mt (protection covers included)	8-41100185		
	<b>Kit</b> of 4 rubber blocks (4 pcs.) H = 80 mm.	8-42300027		
	Angle pipe protection cover.	8-41100143		
	In-pit installation kit for lifts with flaps, incl. support for flaps that must be bolted to the ground - mandatory for recessed installation	8-41100165		





# **DOUBLE SCISSORS LIFTS - HIGH PROFILE**



# CCC 372 I E





- -Capacity: 3.600 kg.
- -Electrohydraulic underbody double scissors lift, for tyre specialists, car workshops, and body repairers.
- -Alignment of the runboards with the MASTER/SLAVE system.
- -Runboard available with extensions only. Configuration for pit installation.





Code	Power Supply	Description	
0-41106300/15	230/400V - 3Ph - 50/60Hz	TECO C372   E	
0-41106302/15	230V - 1Ph - 50Hz	TECO C372 I E	
0-41106303/15	230V - 1Ph - 60Hz	TECO C372 I E	
8-41600192		Customization kit (Compulsory)	





# **DOUBLE SCISSORS LIFTS - HIGH PROFILE**



# CCC C412 I E





- -Capacity: 4.000 kg.
- -Electrohydraulic underbody double scissors lift, for tyre specialists, car workshops, and body repairers.
- -Alignment of the runboards with the MASTER/SLAVE system.
- -Runboard available with extensions only. Configuration for pit installation.





Code	Power Supply	Description	
0-41106400/15	230/400V - 3Ph - 50/60Hz	TECO C412 I E	
0-41106402/15	230V - 1Ph - 50Hz	TECO C412 I E	
0-41106403/15	230V - 1Ph - 60Hz	TECO C412 I E	
8-41600193		Customization kit (Compulsory)	







COMPULSORY ACCESSORIES - TECO C372   E - TECO C412   E			
Image Description Code			
	Set of masonry screws (8 pcs.) For all models in the range.	8-41100203	

OPTIONAL ACCESSORIES - TECO C372   E - TECO C412   E			
Image	Description	Code	
	Off-the-road vehicle cross bar (2 pcs).	8-42300047	
	Flush installation frame set for lifts with flaps	8-41100204	







OPTIONAL ACCESSORIES - TECO C372   E - TECO C412   E			
Image	Description	Code	
	Extensions for pipes and cables L= 1 mt (protection covers included)	8-41100184	
	Extensions for pipes and cables L= 2 mt (protection covers included)	8-41100185	
	<b>Kit</b> of 4 rubber blocks (4 pcs.) H = 80 mm.	8-42300027	





# PLATFORM SCISSORS LIFTS FOR WHEEL ALIGNMENT - LOW PROFILE







#### Main features:

- -Capacity: 5.500 kg.
- -Electrohydraulic underwheel scissors type lift for total wheels geometry control "CT" with: rear oscillating platforms e recesses for front turntables.
- -Auxiliary wheel release lift "LT".
- -Lift table with double lifting cylinder to ensure a constant parallel lift movement.



**DELIVERY AVAILABLE FROM CHINA ONLY** 









Code	Power Supply	Description				
TECO 5500C SE	TECO 5500C SERIES, CAPACITY 5500 KG, RUNWAY LENGHT 4600 MM					
0-42116000/15	230-400V/3Ph/50-60Hz	TECO 5500C CT LT, with LT lift table, runway length 4600 mm				
8-42600163		Customization kit - TECO 5500C CT LT, compulsory				
0-42112100/15	230-400V/3Ph/50-60Hz	TECO 550C CT, runway length 4600 mm				
8-42600164		Customization kit - TECO 5500C CT, compulsory				
0-42112300/15	230-400V/3Ph/50-60Hz	TECO 5500C, runway length 4600 mm				
8-42600166		Customization kit - TECO 5500C, compulsory				
0-42116010/15	230-400V/3Ph/50-60Hz	TECO 5500C CT LT I, with LT lift table, runway length 4600 mm, in-pit installation				
8-42600223		Customization kit - TECO 5500C CT LT I, compulsory				
0-42112110/15	230-400V/3Ph/50-60Hz	TECO 5500C CT I, runway length 4600 mm, in-pit installation				
8-42600226		Customization kit - TECO 5500C CT I, compulsory				
0-42112310/15	230-400V/3Ph/50-60Hz	TECO 5500C I, runway length 4600 mm, in-pit installation				
8-42600229		Customization kit - TECO 5500C I, compulsory				
TECO 5500C SE	TECO 5500C SERIES, CAPACITY 5500 KG, RUNWAY LENGTH 5200 MM					
0-42116500/15	230-400V/3Ph/50-60Hz	TECO 5500C CT LT, with LT lift table, runway length 5200 mm				
8-42600219		Customization kit - TECO 5500C CT LT, compulsory				
0-42116600/15	230-400V/3Ph/50-60Hz	TECO 5500C CT, runway length 5200 mm				
8-42600220		Customization kit - TECO 5500C CT, compulsory				
0-42116800/15	230-400V/3Ph/50-60Hz	TECO 5500C, runway length 5200 mm				
8-42600221		Customization kit - TECO 5500C, compulsory				
0-42116510/15	230-400V/3Ph/50-60Hz	TECO 5500C CT LT I, with LT lift table, runway length 5200 mm, in-pit installation				
8-42600224		Customization kit - TECO 5500C CT LT I, compulsory				
0-42116610/15	230-400V/3Ph/50-60Hz	TECO 5500C CT I, runway length 5200 mm, in-pit installation				
8-42600227		Customization kit - TECO 5500C CT I, compulsory				
0-42116810/15	230-400V/3Ph/50-60Hz	TECO 5500C I, runway length 5200 mm, in-pit installation				
8-42600230		Customization kit - TECO 5500C I, compulsory				



# PLATFORM SCISSORS LIFTS FOR WHEEL ALIGNMENT - LOW PROFILE







#### Main features:

- -Capacity: 4.500 kg.
- -Electrohydraulic underwheel scissors type lift for total wheels geometry control "CT" with: rear oscillating platforms e recesses for front turntables.
- -Auxiliary wheel release lift "LT".
- -Lift table with double lifting cylinder to ensure a constant parallel lift movement.



DELIVERY AVAILABLE FROM CHINA ONLY









Code	Power Supply	Description				
TECO 4500C SE	TECO 4500C SERIES, CAPACITY 4500 KG, RUNWAY LENGTH 4200 MM					
0-42116100/15	230-400V/3Ph/50-60Hz	TECO 4500C CT LT, with LT lift table, runway length 4200 mm				
8-42600167		Customization kit - TECO 4500C CT LT, compulsory				
0-42116200/15	230-400V/3Ph/50-60Hz	TECO 4500C CT, runway length 4200 mm				
8-42600168		Customization kit - TECO 4500C CT, compulsory				
0-42116400/15	230-400V/3Ph/50-60Hz	TECO 4500C, runway length 4200 mm				
8-42600170		Customization kit - TECO 4500C, compulsory				
0-42116110/15	230-400V/3Ph/50-60Hz	TECO 4500C CT LT I, with LT lift table, runway length 4200 mm, in-pit installation				
8-42600222		Customization kit - TECO 4500C CT LT I, compulsory				
0-42116210/15	230-400V/3Ph/50-60Hz	TECO 4500C CT I, runway length 4200 mm, in-pit installation				
8-42600225		Customization kit - TECO 4500C CT I, compulsory				
0-42116410/15	230-400V/3Ph/50-60Hz	TECO 4500C I, runway length 4200 mm, in-pit installation				
8-42600228		Customization kit - TECO 4500C I, compulsory				







OPTIONAL ACCESSORIES - TECO 5500C - TECO 4500C						
Image	Description	Code				
	<b>Set</b> of cross bars, to be ordered with the lift, compulsory for usage of 2 jacking beams, recommended for wheel alignment, standard colour grey RAL 7016 fixed	8-42100218				
	Off-the-road vehicle cross bar (2 pcs).	8-42300047				
	Kit of 4 rubber blocks (4 pcs.) H = 80 mm.	8-42300027				
	Complete loe-voltage lighting kit	8-42100185				
	Extensions for pipes and cables L= 2 mt (for lift with LT)	8-42100183				
	Extensions for pipes and cables L= 4 mt (for lift with LT)	8-42100184				
	Extensions for pipes and cables L= 2 mt (for lift without LT)	8-42100173				
	Extensions for pipes and cables L= 4 mt (for lift without LT)	8-42100174				







OPTIONAL ACCESSORIES - TECO 5500C - TECO 4500C						
Image	Description	Code				
	Scissor Jack 2,2 ton. Gray Ral 7016	J804-0000000				
IMAGE NOT AVAIABLE	Transformation kit from surface-mounted to recessed installation	8-42100234/00				











